



HYPER VINYROCK SHIELD

-JAPANESE STANDARD HIGH QUALITY-


Product name	HYPER VINYROCK SHIELD
Paint type	Water based silicone resin
Use	Exterior and Interior
Gloss Type	Semi-gloss Full-gloss
Color match	JPMA Color card & other card
Coating of amount	0.11-0.13kg/m ² • 1coat
No of Coat	2-3coat
Tools	Brush , Roller
Dilution	clean water
Dilution ratio	10-20%
Touch Dry	30min
Hard Dry	2h
Coating Interval	2h
Specific gravity	1.15±0.03
Package	18kg, 3kg
Sealer of Exterior	VINYROCK CATIONIC SEALER
Mid coat of Exterior	VINYROCK ELASTIC FILLER




Process	Paint & Method		Dilution ratio		Coating amount Kg/m ² • 1coat	Coating Interval
Surface Preparation	1) Remove completely Efflorescence, Laitance, Dust, Dirt etc.. by wire brush.					
	2) Dry well until water content below 10% and pH below 9.5, then start painting.					
Under coat	Product	VINYROCK CATIONIC SEALER	Not necessary	Brush Roller Airless	0.06 - 0.10kg	3hours <
	Tools	Brush, Roller, Airless				
	No. of coat	1coat				
	Coating amount	150 - 250m ² /15kg/1coat				
Mid coat	Product	VINYROCK ELASTIC FILLER	Clean Water	Mid Hair Roller	5 - 8%	0.5 - 0.8kg
	Tools	Roller,Airess		Mastic Pattern Roller	2 - 5%	0.8 - 1.5kg
	No. of coat	1 - 2coat				4hours <
	Coating amount	10 - 32m ² /16kg/1coat				
Top coat	Product	HYPER VINYROCK SHEILD	Clean water	Brush Roller Airless	10 - 20% 10 - 20% 15 - 25%	0.11 - 0.13kg
		HYPER VINYROCK SHEILD GLOSS				
	Tools	Brush, Roller				
	No. of coat	2 - 3coat				
	Coating amount	115 - 135m ² /15kg/1coat				

Japanese Standard

Anti Alga Test (4weeks)



No Anti Alga Type



HYPER
VINYROCK
SHIELD

Anti Mold Test (2weeks)



No Anti Mold
Type



HYPER
VINYROCK
SHIELD

Gloss Type




HYPER
VINYROCK
SHIELD

HYPER
VINYROCK
SHIELD
GLOSS


【Washability】

Anti-Electrification monomer & smooth surface gives less dirt



Substrate Film

Self Cleaning keeps beauty long



Substrate Film


Water

Dirt

【Anti alga & mold】

【Mechanism of medicine holding】

Anti alga & mold agent




Special holding material which designed in molecular level gives less leaking agent and keep performance long.

【High Durability】

High Durability

【Protect from deterioration factor】

Hybrid special bridging protect building from deterioration factor such as UV, IR(heat), weather, environmental etc..



【High durability, Wash ability, Anti alga & mold】

【HYPER VINYROCK SHIELD】

HYPER VINYROCK SHIELD series is a multi function water based silicon resin paint which is developed & hybrid by ROCK PAINT's resin synthesis technology.

It has excellent high durability under different condition, special medicine holding technology of anti alga & mold agent, and excellent wash ability by surface controlling in molecular level and anti-electrification monomer.

HYPER VINYROCK SHIELD is 30% gloss type (semi-gloss), HYPER VINYROCK SHIELD is full gloss type.

It is possible to have excellent performance by combination of VINYROCK CATIONIC SEALER (excellent penetration & adhesion), and VINYROCK ELASTIC FILLER (semi-elastic & texture).

Variety of colors



Choose your taste color and Enjoy your lifestyle!
JPMA COLOR CARD 624colors
by Japan paint manufactures association





HYPYER VINYROCK SHIELD

-JAPANESE STANDARD HIGH QUALITY-

製品名	HYPYER VINYROCK SHIELD
塗料種類	水性シリコン樹脂塗料
用途	内装及び外装
ツヤ	3分ツヤあり(30%Gloss)
調色可能見本	ロックペイントカラーカード他
塗布量	0.11-0.13kg/m ² ・1回
塗装回数	2-3回
塗装用具	ハケ、ローラー
希釈材	清水
希釈率	10-20%
指触乾燥	30分
硬化乾燥	2時間
塗り重ね可能時間	2時間
容量	18kg,3kg
内外装用下塗り材 (新設、塗替え)	VINYROCK CATIONIC SEALER
内外装用下塗り材 (新設のみ)	VINYROCK SEALER CONC
外装中塗り材	VINYROCK ELASTIC FILLER

HYPYER VINYROCK SHIELD

水性シリコン樹脂塗料

内装及び外装

3分ツヤあり(30%Gloss)

ロックペイントカラーカード他

0.11-0.13kg/m²・1回

2-3回

ハケ、ローラー

清水

10-20%

30分

2時間

2時間

18kg,3kg



VINYROCK CATIONIC SEALER

VINYROCK SEALER CONC

VINYROCK ELASTIC FILLER




標準塗装仕様:耐クラック対応

工程	塗料及び作業内容	希釈率	塗布量 Kg/m ² ・1回	塗り重ね 可能時間
素地調整	1) チョーキング、レイタス、埃、汚れ等のワイヤーブラシで除去します。 2) pHは9.5以下の水は10%以下になるまで乾燥させてください。			
下塗	製品名	VINYROCK CATIONIC SEALER	通常 不要	0.06 - 0.10kg 3時間以上
	塗装用具	ハケ、ローラー、エアレス		
	塗装回数	1回		
	塗布量	150 - 250m ² /18kg/1回		
中塗	製品名	VINYROCK ELASTIC FILLER	清水	0.5 - 0.8kg 4時間以上
	塗装用具	ハケ、ローラー		
	塗装回数	1 - 2coat		
	塗布量	10 - 32m ² /16kg/1coat		
上塗	製品名	HYPYER VINYROCK SHEILD	清水	0.11 - 0.13kg 2時間以上
	塗装用具	ハケ、ローラー		
	塗装回数	2 - 3回		
	塗布量	115 - 135m ² /15kg/1回		

Japanese Standard


防藻テスト(4週間)



防藻剤なしの塗料

HYPER VINYROCK SHIELD

防カビテスト(2週間)



防カビ剤なしの塗料 HYPER VINYROCK SHIELD

Gloss Type



HYPER
VINYROCK
SHIELD

HYPER
VINYROCK
SHIELD
GLOSS

【低汚染】

帯電防止モノマー成分配合により、緻密な表面構造となるため、汚れが付着しにくい。




セルクリーニング技術により
キレイさが長持ち!

【防藻・防カビ】

~薬剤の包封化のメカニズム~

防藻・防カビ剤



分子レベルで操作された包封化特殊
成分により、防藻・防カビ剤が溶出し
にくく、その効果が持続。

【高耐久】

高耐候性

【劣化要因から建物を守ります。】

リアルハイブリッドによる特殊架橋により、塗膜の劣化要因である紫外線(UV)、赤外線(熱)、気候要因、環境要因から建物を守ります。



【高耐久、低汚染、防藻・防カビ】

【ハイパービニロックシールド】

ハイパービニロックシールドは、ロックペイントがこれまで培ってきた樹脂技術を用いて、ハイブリット配合した各種性能に優れる多機能水性シリコン塗料です。

様々な環境下における耐候性、薬剤包材化特殊技術による防藻・防カビ機能、表面の流動性を分子レベルでコントロールし、帯電防止モノマーとのW効果により低汚染性を発揮します。

ハイパービニロックシールドは3分ツヤ、ハイパービニロックシールド グロスはツヤ有と様々な仕上げが可能です。

浸透性と密着力に優れるビニロックカチオンシーラー、微弾性・意匠性に優れるビニロックエラスティックフィラーと組み合わせることで複合的に高性能を発揮します。

Variety of colors



Choose your taste color and Enjoy your lifestyle!
JPMA COLOR CARD 624colors
by Japan paint manufacturers association



PT.ROCKPAINT INDONESIA

JL. HARAPAN IV LOT KK-9B, KAWASAN INDUSTRI KIIC,
DESA SIRNABAYA, KECAMATAN TELUK JAMBE TIMUR,
KARAWANG 41361, JAWA BARAT TEL +62-21-8911-4321



PT.ROCKPAINT INDONESIA
ROCKPAINT.CO.LTD

HYPYER VINYROCK SHIELD

-STANDAR KUALITAS TINGGI JEPANG-



Nama Produk	HYPYER VINYROCK SHIELD
Tipe Cat	Water based silicone resin
Penggunaan	Eksterior and Interior
Tipe Gloss	Semi-gloss (30%)
Kombinasi Warna	JPMA Color card & other card
Jumlah Lapisan	0.11-0.13kg/m ² / 1 kali pengecatan
Jumlah Cat	2-3 kali pengecatan
Alat Aplikasi	Kuas , Roller
Pengenceran	Air Bersih
Persentase Pengenceran	10-20%
Cepat Kering	30 menit
Sulit Kering	2 jam
Jarak Waktu Pengecatan	2 jam
Kemasan	18kg, 3kg
Eksterior Sealer	VINYROCK CATIONIC SEALER
Eksterior Lapisan Tengah	VINYROCK ELASTIC FILLER


Daya Tahan Tinggi	Anti Lumut & Jamur
Baunya Tidak Menyengat	Mudah dibersihkan
Multi Fungsi	Tahan Terhadap Cuaca
Hiding Power kuat	



Proses	Cat & Metode		Persentase Pengenceran			Jumlah Lapisan Kg/m ² /1 kali pengecatan	Jarak Waktu Pengecatan				
Persiapan Permukaan	1) Bersihkan permukaan yang akan dicat dari karat, debu, kotoran, dll dengan menggunakan sikat kawat										
	2) Keringkan hingga kadar air di bawah 10% dan pH dibawah 9.5, lalu mulai pengecatan.										
Lapisan Bawah	Produk	VINYROCK CATIONIC SEALER	Tidak Perlu	Sikat Roller Airless	-	0.06 - 0.10kg	3jam <				
	Alat Aplikasi	Sikat, Roller, Airless									
	Jumlah Pengecatan	1 kali pengecatan									
	Jumlah Lapisan	150 - 250m ² /15kg/1 kali pengecatan									
Lapisan Tengah	Produk	VINYROCK ELASTIC FILLER	Air Bersih	Mid Hair Roller	5 - 8%	0.5 - 0.8kg	4jam <				
	Alat Aplikasi	Roller,Airess			2 - 5%	0.8 - 1.5kg					
	Jumlah Pengecatan	1 – 2 kali pengecatan		Mastic Pattern Roller							
	Jumlah Lapisan	10 - 32m ² /16kg/1 kali pengecatan									
Lapisan Atas	Produk	HYPYER VINYROCK SHEILD	Air Bersih	Sikat Roller Airless	10 - 20%	0.11 - 0.13kg	2jam <				
		HYPYER VINYROCK SHEILD GLOSS									
	Alat Aplikasi	Sikat, Roller									
	Jumlah Pengecatan	2 – 3 kali pengecatan			15 - 25%						
	Jumlah Lapisan	115 - 135m ² /15kg/1 kali pengecatan									

Standar Jepang

Tes Anti Lumut (4 minggu)



Tes Anti Jamur (2 minggu)




Tipe Gloss




HYPER VINYROCK SHIELD 30% Gloss

HYPER VINYROCK SHIELD 70% GLOSS

【Washability】



【Anti alga & mold】



Special holding material which designed in molecular level gives less leaking agent and keep performance long.

【High Durability】

High Durability

【Protect from deterioration factor】

Hybrid special bridging protect building from deterioration factor such as UV, IR(heat), weather, environmental etc..



【Daya Tahan Tinggi, Mudah dibersihkan, Anti lumut & jamur】

【HYPER VINYROCK SHIELD】

HYPER VINYROCK SHIELD adalah cat yang berbahan dasar *resin* silikon yang dikembangkan dan diolah dengan teknologi *resin synthesis* Rock Paint.

Memiliki ketahanan terhadap berbagai macam cuaca, anti jamur dan lumut yang ditangani oleh teknologi *special medicine*, serta mudah dibersihkan karena permukaannya terkontrol oleh tingkat molekul dan monomer anti elektrifikasi.

HYPER VINYROCK SHIELD merupakan *semi gloss* dengan *gloss* 30%, Bisa memiliki tampilan yang sangat baik dengan kombinasi dari VINYROCK CATIONIC SEALER (penyerapan dan perekat yang sangat baik) dan VINYROCK ELASTIC FILLER (Semi elastis dan tekstur)

Variasi Warna



Pilihlah warna sesuai seleramu dan nikmati gaya hidupmu!

JPMA COLOR CARD 624 warna

Oleh: Japan paint manufactures association



PT.ROCKPAINT INDONESIA

JL. HARAPAN IV LOT KK-9B, KAWASAN INDUSTRI KIIC,
DESA SIRNABAYA, KECAMATAN TELUK JAMBE TIMUR,
KARAWANG 41361, JAWA BARAT TEL +62-21-8911-4321



PT.ROCKPAINT INDONESIA
ROCKPAINT.CO.LTD